


FPR100

1" Flush Panel with Reveal


PRODUCT DESCRIPTION

- Flush panel system designed for use in soffit, mansard and wall applications
- 14-inch flush panel system that yields a 1-inch reveal in the panel profile
- Adds depth, texture, and additional strength to the panel profile

1" Flush Panel with Reveal; max width 14.0"; concealed, interlocking seams fastened with (2) #10-12 x 1" long No. 2 Phillips drive pancake head, wood screws; fastening metal to panel to Wood or Steel Substrate; maximum 12" fastener spacing; Panel Rollformer: Schleichbach Quadro-Plus Rollformer; *Oil Canning is not a Cause for Rejection*



www.sentrigard.com



DESIGN INFORMATION

- Vertical or Horizontal Application
- Actual Panel Width: 14" from 20" Coil
- Solid Substrate or Open Framing
- Architectural Soffit/Wall Panel w/Reveal
- Concealed Fastener Attachment – No Clip Required
- 24 and 26 Gauge Galvalume®
- .032" Aluminum
- 16oz Copper
- 30 Year Finish Warranty on Kynar 500 Finish
- Weather Tight Warranty Not Available
- Underlayment Not Required
- Vented or Non-Vented

TEST REPORT SUMMARY

- No Testing Performed